



Direct Window Supplies Ltd — Bay QUOTE ☐ or ORDER ☐

The Old Bakery, Kiln Lane, Swindon, SN2 2NP
Tel: 01793 541154 Fax: 01793 541114
sales@directwindows.co.uk

ORIGINAL QUOTE #:

CIRCLE OPTIONS BELOW AS REQUIRED (STANDARDS UNDERLINED)

Frame Type:	<u>Chamfered</u> / Ovolo
Bead Type:	Chamfered / <u>Ovolo</u>
Sash Type:	<u>Standard</u> / Flush
Colour:	<u>White</u> / Cherry / Oak Cherry on White / Oak on White Other — OUTSIDE: _____ INSIDE: _____
Outer Frame:	<u>Standard (55mm)</u> / Wide (75mm)
Energy Rating:	<u>A Rated</u> / B Rated / C Rated / UNGLAZED
Handle Colour:	<u>White</u> / Black / Gold Bright Chrome / Satin Chrome
Window Locks:	<u>Encloser + Hinge Guard</u> / Espag
Window Hinges:	<u>Fire Egress</u> / Easy Clean / Restrictor
Door Handles:	<u>Lever-Lever</u> / Lever-Pad Lever-Lever Split Spindle
Door Threshold:	<u>Standard PVC (75mm)</u> / Slim PVC (55mm) Part-M PVC (For Cill) / Part-M Ali (For Cill) Part-M Ali (No Cill)
Door Options:	<u>Restrictor Stay (Open Out)</u> / Basic Cylinder
Document Q	<u>Not Required</u> / Required


- All frames viewed from the outside.
- Point of triangle shows hinge position.
- If Georgian / Lead is required, show design clearly.
- For Document Q, show laminated glass requirements.
- Delivery subject to our standard cut-off & lead times.

All product information is freely available from our website

www.directwindows.co.uk

DWS Bay Quote Form — V2.6 (March 2022)

Customer Name:	Delivery Address:	Page: of
Address:		Date:
		Reference:
		Date Required:
Tel:	Fax:	Email:

PLEASE CLEARLY SHOW YOUR BAY DETAILS NEXT TO THE SAMPLE, ALL MEASUREMENTS MUST BE INTERNAL AND INCLUDE CILL, POLES AND ANY EXTENDERS. 						YOUR BAY LAYOUT:				
Sketch Design	O/A Width	O/A Height	Mullion Break	Transom Drop	Cill	Glass / Panel	Door Opening	Frame Extenders	Trickle Vents	
Location Name						Obs & Panel Detail		INC In O/A Sizes	For Doc F	
1			<u>610</u>	<u>400</u>	85 <u>150</u> 180 NONE		IN OUT		<u>YES</u> NO	
2			<u>610</u>	<u>400</u>	85 <u>150</u> 180 NONE		IN OUT		<u>YES</u> NO	
3			<u>610</u>	<u>400</u>	85 <u>150</u> 180 NONE		IN OUT		<u>YES</u> NO	
4			<u>610</u>	<u>400</u>	85 <u>150</u> 180 NONE		IN OUT		<u>YES</u> NO	
5			<u>610</u>	<u>400</u>	85 <u>150</u> 180 NONE		IN OUT		<u>YES</u> NO	
6			<u>610</u>	<u>400</u>	85 <u>150</u> 180 NONE		IN OUT		<u>YES</u> NO	

NOTES:

For DOC F we will place the maximum number of trickle vents possible into each window/door upto a maximum of 10,000mm² EA, unless told otherwise.

Before ordering please ensure that you are familiar with our products and specifications. We will not accept any responsibility for want of knowledge in the event that items do not meet with your requirements. Please be aware that products are updated regularly.

SIGNED: _____

PRINT: _____ DATE: _____